

In-line holders



SZ 7101



SZ 7105



SZ 7108

SZ 7101

In-line holder

Body: PVC. Sensor Diameter: 12 mm. Sensor Length: 110 mm

Operating Temperature: 40 °C max.

Operating Pressure: 10 bar max. at 20 °C

Fixing: 1/2" BSP for pipe 1" minimum

Dimensions: L = 110 mm Diameter = 25 mm

Applications: installation in 1" pipe

SZ 7105

In-line holder

Body: PVDF. Sensor Diameter: 12 mm. Sensor Length: 110 mm

Operating Temperature: 100 °C max.

Operating Pressure: 10 bar max. at 50 °C

Fixing: 1/2" BSP for pipe 1" minimum

Dimensions: L = 110 mm Diameter = 25 mm

Applications: installation in 1" pipe

SZ 7108

In-line holder

Body: 316 S.Steel. Sensor Diameter: 12 mm.

Sensor Length: 110 mm

Operating Temperature: 110 °C max.

Operating Pressure: 10 bar max. at 50 °C

Fixing: 1/2" BSP for pipe 1" minimum

Dimensions: L = 110 mm Diameter = 25 mm

Applications: installation in 1" pipe

Flow cells

SZ 7231 - SZ 7261

Flow cell for 1 sensor

SZ 7251

Autoclean flow cel

SZ 7233 - SZ 7263

Flow cell for 4 sensors



Submersible holders



SZ810

Immersion probe, L=210 mm PVC

SZ820

Immersion probe, L=400 mm PVC

SZ821

Immersion probe, L=400 mm PVDF

SZ860

Immersion probe, L=720 mm PVC

SZ880

Immersion probe, L=1170 mm PVC

SZ8603

Immersion probe, L=720 mm PP

SZ8803

Immersion probe, L=1170 mm PP

SZ8608

Immersion probe, L=720 mm AISI 316

SZ8808

Immersion probe, L=1170 mm AISI 316

SZ862

Immersion probe, L=720 mm PVC
low cost type

SZ882

Immersion probe, L=1170 mm PVC
low cost type